

# MATERIAL SAFETY DATA SHEET

Page 1 of 4

Product Name: **WRAP SEAL QUICK REPAIR KIT FOR PIPE LEAKS**

MSDS No: 100A

Revision No: 6

Issue Date: 17 April 2015

## Section 1 – Company Details

**Company Name:** SealXpert™ Products

**Address:** 60 Kaki Bukit Place #09-11 Eunos Techpark  
Singapore 415979

**Tel:** +65 6742 4992/6742 4998

**Fax:** +65 6749 6916

**Email:** mailbox@sealxpert.com

## Section 2 – Composition

INGREDIENTS	CAS No	%	EXPOSURE LIMITS
Fiberglass	65997-17-3	48 - 52	10mg/m3
Polypropylene polyol diphenyl methane di-isocyanate prepolymer	9048-57-1	40 - 42	N/A
Amine catalyst	6425-39-4	1 - 5	0.051 mg/m3
Methanesulfonic acid	75-75-2	< 1	0.051 mg/m3

Source of exposure limit data – ACGIHTreshold Limit Values

Abbreviations : N/A – Not Applicable

## Section 3 – Hazards Identification

**Hazards Identification:** Non-hazardous Substance. Not classified as dangerous goods.

Non-Hazard classification according to the criteria of NOHSC.

Non-dangerous goods classification according to the Singapore Code for Transport of Dangerous Goods.

**Human Health Hazards:** May cause sensitization by contact with eye.

**Safety Hazards:** Avoid contact with eye.

**Environmental Hazards:** Non-toxic to aquatic organisms

**Other Information:** The use of shears is recommended to remove old product from pipes so as to minimize dust formation.

## Section 4 – First Aid Measures

**Inhalation:** Provide fresh air. If breathing becomes difficult, call physician.

**Skin:** S24: Avoid contact with skin.  
Wash thoroughly with soap and water.

**Eye:** S25: Avoid contact with eye.  
S26: In case of contact with eyes, rinse immediately with plenty of water and consult a physician.

**Ingestion:** S46: If swallowed, seek medical advice immediately and show this container or label.  
S2: Keep out of reach of children.  
Unlikely route of entry.

# MATERIAL SAFETY DATA SHEET

Page 2 of 4

Product Name: **WRAP SEAL QUICK REPAIR KIT FOR PIPE LEAKS**

MSDS No: 100A

Revision No: 6

Issue Date: 17 April 2015

## Section 5 – Fire Fighting Measures

<b>Specific Hazards:</b>	Nil.
<b>Extinguishing Media:</b>	H2O spray, foam, CO2, dry chemicals or foam
<b>Unsuitable Extinguishing Media:</b>	Nil
<b>Protective Equipment:</b>	Firefighters to wear self-contained breathing apparatus and full protective clothing.
<b>Other Information:</b>	Keep undamaged product cool with H2O fog while fighting fire.

## Section 6 – Accidental Release Measures

<b>Personal Precautions</b>	Remove all possible sources of ignition in the surrounding area.
<b>Environmental Precautions</b>	Prevent from spreading or entering into drains and surface waters (e.g. lakes, ponds, ditches, rivers and streams) by using sand, earth, or other appropriate non-combustible barriers.
<b>Clean-up Methods - Small Spillages</b>	To minimize soil and groundwater contamination, absorb liquid with sand earth or other recommended absorbent material. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.
<b>Clean-up Methods - Large Spillages</b>	Prevent from spreading by making a barrier with sand, earth or other containment material. Dispose of as for small spills.
<b>Maritime Spillages</b>	Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.
<b>Other Information</b>	Observe all relevant local regulations.

## Section 7 – Handling and Storage

<b>Handling:</b>	S37/ S39: Wear protective glove and safety glasses while handling uncured product. Uncured product will adhere to clothing. Maintain high standards of personal hygiene, washing hands after coming in contact with product. S24/ S25: Avoid eye and skin contact.
<b>Storage:</b>	S3: Store in cool, dry and well-ventilated area out of direct sunlight. Store away from all heat sources. Optimum storage conditions 4 - 30°C. For best results, rotate stock.

## Section 8 – Exposure Controls / Personal Protection

INGREDIENTS	CAS No	%	EXPOSURE LIMITS
Fiberglass	65997-17-3	48 - 52	10mg/m <sup>3</sup>
Polypropylene polyol diphenyl methane di-isocyanate prepolymer	9048-57-1	40 - 42	N/A
Amine catalyst	6425-39-4	1 - 5	0.051 mg/m <sup>3</sup>
Methanesulfonic acid	75-75-2	< 1	0.051 mg/m <sup>3</sup>

Source of exposure limit data – ACGIH Threshold Limit Values

Abbreviations : N/A – Not Applicable

# MATERIAL SAFETY DATA SHEET

Page 3 of 4

Product Name: **WRAP SEAL QUICK REPAIR KIT FOR PIPE LEAKS**

MSDS No: 100A

Revision No: 6

Issue Date: 17 April 2015

**Respiratory Type:** Avoid breathing of dust, vapours, mists or spray. Where ventilation is inadequate and dusts, vapours or mists are generated the use of a respirator with filter is recommended. Filter capacity and respirator type depends on exposure levels.

**Eye Protection:** S39: eye/ face protection. Non-fogging chemical safety goggles or safety glasses with side shields.

**Glove Type:** S37: Wear suitable impervious protective gloves such as PVC or Nitrile gloves.

**Clothing :** S36: Wear suitable impervious protective clothing.

## Section 9 – Physical and Chemical Characteristics

### APPEARANCE

**Physical:** Tacky resin on a fiberglass substrate

**Colour :** White or Yellowish

**Odour :** Very slight

**Boiling Point :** N/A

**Vapour Pressure :** N/A

**Vapour Density (AIR = 1) :** N/A

**Solubility in Water :** Nil

**Specific Gravity :** 1.23 at 43°C

**Melting Point :** N/A

**Evaporation Rate :** N/A

## Section 10 – Stability and Reactivity

**Stability:** Stable

**Products to Avoid:** None

**Hazardous Reactions:** None

**Hazardous Decomposition:** None

## Section 11 – Toxicological Information

ROUTE OF ENTRY	DESCRIPTION	MINIMUM CONCENTRATION FOR EFFECT
Inhalation	R20: Harmful by inhalation. Isocyanate vapours of uncured material below detectable limits.	N/A
Skin	R42/43: May cause sensitization by inhalation and skin contact. Contact (Employing modified human draize test): Product is neither an irritant nor an allergen. Adsorption: Acute dermal LD50 > 2g/kg, no reaction at this dose.	N/A
Eyes	R36/37/38: Irritating to eyes, respiratory system and skin. Avoid contact; uncured material is not expected to be irritant when used as directed	N/A
Ingestion	Oral LD50 > 5g/kg; no mortalities or untoward behavioural reactions observed.	N/A

### Carcinogenicity

# MATERIAL SAFETY DATA SHEET

Page 4 of 4

Product Name: **WRAP SEAL QUICK REPAIR KIT FOR PIPE LEAKS**

MSDS No: 100A

Revision No: 6

Issue Date: 17 April 2015

**NTP** N/A

**IARC Monographs** N/A

**OSHA Regulated** N/A

## Signs And Symptoms Of Exposure

**Eyes:** Irritation

**Skin :**Minor irritation

## Medical Conditions Aggravated By Exposure:

Open cuts or abrasions or rashes on skin

## Section 12 – Ecological Information

**Ecotoxicity:** Non-toxic to aquatic organisms.

**Mobility:** Floats on water. Does not contains volatile components.

**Persistence/Degradability:** Components are inherently biodegradable.

**Bioaccumulation:** Nil

## Section 13 – Disposal Considerations

**Waste Disposal :** Solid waste landfill or authorized incineration

## Section 14 – Transport Information

**Transportation:** Not classified as Dangerous Goods according to Singapore Code for Transport of Dangerous Goods by Road, Rail and Air.

## Section 15 – Regulatory Information

None known

## Section 16 – Other Information

**Other Precautions:** Removal of old bandages with oscillating saws without adequate ventilation will potentially cause irritant dusts to be generated into atmosphere. The use of shears is recommended to remove old product from pipes so as to minimize dust formation.

### Warning to users:

This data sheet completes the technical notices but does not supersede them. The information contained in it is grounded to the statement of our knowledge of the product concerned at the publishing date.

Moreover, user's attention should be drawn on the possible risks incurred when a product is used for other purposes than those for which it has been designed. It does not stop in any case the user knowing and following the whole regulatory texts related to his activity. He will be the sole responsible of the precautions related to the use of the products he knows.

The aim of the whole regulatory prescriptions mentioned is to help the receiver to fulfill his duties when using the product. This list must not be considered as exhaustive. It does not stop the user from making sure that he complies with the written obligations other than those previously cited and which rule the fact of keeping and using the product for which he is the sole responsible person.