

Introduction

SealXpert® Underwater Petro Paste is soft brown paste which may be applied underwater by gloved hand, stiff bristle brush or roller. A petrolatum based compound for the preparation of metal surfaces underwater prior to the application of SealXpert® Petro Tapes. It deposits a layer of protective compound onto the surface such that water is displaced and voids filled when the tape is applied.

SealXpert® Underwater Petro Paste can be applied to marginally prepared surfaces (SSPC SP 2-3), applied to very wet or underwater surfaces and it contains no Volatile Organic Compounds. SealXpert® Underwater Petro Paste can be applied by inexperienced personnel and no shut downs or cure time is necessary. SealXpert® Underwater Petro Paste meets AWWA C-217 standards

Typical Properties

Typical Properties	Data
Solid Content	100%
Flash Point	>180°C
Specific Gravity	1.08
Specific Volume	925cc/kg
Coverage	2-5m ² /kg
Temperature Range	
For Application	5°C
For Service	-25°C to 50°C

Surface Preparation

Prepare surfaces by removing all loose scale, rust or other foreign matter in accordance to SSPC SP2 "Hand Tool Cleaning" or SP3 "Power Tool Cleaning". High pressure water wash of 3,000 - 7,000 psi is also suitable. Surfaces should be free from mud, loose rust, scale, flaking coatings and marine growth.

Apply a thin uniform coat of SealXpert® Underwater Petro Paste to entire surface with gloved hand, brush or roller.

Packaging

2.5kg pails
25kg drums

Disclaimer: The information contained herein is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained by the use thereof, or that any such use will not infringe any patent. Before using, user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith.